# JC11 Rec'd PCT/PTO 1 5 MAR 2001

				963.11000.1111			
FORM PTO-1	390	U.S. DEPA	ATTORNEY'S DOCKET NUMBER				
; ?	DES	ISMITTAL LETTER <sup>.</sup> SIGNATED/ELECTE NCERNING A FILING	50060-044				
* <u></u>	×			U.S. APPLIC. NO. (if known, see 37°CFR 1.5) 0 9 / 7 8 7 2 0 4			
INTERNAT	TIONAL A	APPLICATION NO.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED			
-FCT/GB99	√03153	ļ	September 23, 1999	September 23, 1998			
TITLE OF	INVENTION	ON					
TANDEM A	AUDIO C	OMPRESSION					
APPLICAN	√T(S) FOF	R DO/EO/US					
Andrew Ja	mes MAS	SON					
Applicant h	nerewith s	submits to the United States De	esignated/Elected Office (DO/EO/US) the following ite	ems and other information:			
1.	$\boxtimes$	This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371.					
		This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371.					
	$\boxtimes$	This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).					
4. [	$\boxtimes$	A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.					
		A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a.  is transmitted herewith (required only if not transmitted by the International Bureau). b.  has been transmitted by the International Bureau. c.  is not required, as the application was filed in the United States Receiving Office (RO/US)					
. [		A translation of the International Application into English (35 U.S.C. 371(c)(2)).					
		Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) a.  are transmitted herewith (required only if not transmitted by the International Bureau). b. have been transmitted by the International Bureau. c. have not been made; however, the time limit for making such amendment has NOT expired. d. have not been made and will not be made.					
<u>8</u> . [		A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).					
į [		An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).					
<b>4</b> 0. [		A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).					
Items 11. t	o 16. bel	low concern other document(	(s) or information included:				
11.	$\boxtimes$	An Information Disclosure Statement under 37 CFR 1.97 and 1.98.					
12.		An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.					
13.		A FIRST preliminary amendment. A SECOND or SUBSEQUENT preliminary amendment.					
		A substitute specification.					
		A change of power of attorney and/or address letter.					
16.	$\boxtimes$	Other items or information.					
		<ol> <li>International Search Report</li> <li>Cover Sheet of Published In</li> <li>Form PCT/IB/304</li> <li>Form PCT/IB/308</li> <li>Form PCT/IB/332</li> <li>PCT Demand (Form PCT/IP</li> <li>Written Opinion (Form PCT/I</li> <li>Response to Written Opinior</li> <li>International Preliminary Examples</li> </ol>	PEA/401) PIPEA/408) In with Amended Claims amination Report				
			4 10 11 11 11	\$18E5 A DE EN E1 81 31   1 JE 0   1 3 A 0 E			

	(nown, see 37 CFR 1.50)	INTERNATIONAL APPLICATION NO.		ATTORNEY'S DOCKET NUMBER				
09/	787204	PCT/GB99/03153		50060-044				
4-			CALCULATIONS	PTO USE ONLY				
17.   The followin	g fees are submitted:			•				
Basic National F Search Report ha	Fee (37 CFR 1.492(a)(1)-(5) as been prepared by the EF							
International prel	iminary examination fee pai oreliminary examination fee							
but international	search fee paid to USPTO (							
Neither internatio international sear	nal preliminary examination ch fee (37 CFR 1.445(a)(2)							
International preli and all claims sat	iminary examination fee pai tisfied provisions of PCT Art							
		ENTER APPROPRIATE	BASIC FEE AMOUNT =	\$ 860.00				
Surcharge of \$130.00 months from the earlies	Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).							
Claims	Number Filed	Number Extra	Rate					
Total Claims	16 -20 =	0	x \$18.00	\$				
Independent Claims	5 -3=	2	x \$80.00	\$ 160.00				
Multiple dependent cla	im(s) (if applicable)		+ \$270.00	\$				
		TOTAL OF ABO	OVE CALCULATIONS =	\$ 1150.00				
Reduction by 1/2 for fill filed. (Note 37 CFR 1.9	ng by small entity, if applica 9, 1.27, 1.28).	ble. Verified Small Entity	Statement must also be	\$				
		\$ 1150.00						
Fee for recording the e	nclosed assignment (37 CF propriate cover sheet (37 C	R 1.21(h)). The assignme FR 3.28, 3.31). \$40.00 pe	ent must be er property +	\$				
24		тот	AL FEES ENCLOSED =	\$ 1150.00				
			Amount to be: refunded	\$				
3			charged	\$				
a.	check in the amount of \$	to cover the above fe	es is enclosed.					
b. 🛚 Pl	Please charge my Deposit Account No. 500417 in the amount of \$ 1150.00 to cover the above fees. A duplicate copy of this sheet is enclosed.							
c. 🛛 Th Account No.	The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 500417. A duplicate copy of this sheet is enclosed.							
NOTE: Where an app	ropriate time limit under 3 e the application to pendi	37 CFR 1.494 or 1.495 has	s not been met, a petitior	to revive (37 CFR 1.137	(a) or (b)) must be filed			
SEND ALL CORRESPO	ONDENCE TO:		ene 3. Rutius	~				
		SIG	NATURE					
MaDEDMOTT MILL R	EMEDY	e Z. Rubinson						
McDERMOTT, WILL & 600 13 <sup>th</sup> Street, N.W.	EIVIERY		NAME 33,351					
Washington, DC 2000s	5-3096		GISTRATION NUMBER					
(202) 756-8000			March 15, 2001					
Facsimile (202) 756-80	87	E						
BASED ON FORM PTO-	1390 (Rev. 5-93)							

JC02 Rec'd PCT/PTO 1 5 MAR 2

Decket No.: 50060-044

**PATENT** 

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Andrew James MASON

Serial No.:

Group Art Unit:

Filed: March 15, 2001

Examiner:

For:

TANDEM AUDIO COMPRESSION

# PRELIMINARY AMENDMENT

Commissioner for Patents Washington, DC 20231

Sir:

Prior to examination of the above-referenced application, please amend the application as

follows:

IN THE CLAIMS:

Please substitute the attached sheets of amended claims 1 through 16 for the originally filed claims 1 through 17, which includes the cancellation of claim 17.

Please amend newly substituted claims as follows:

Claim 3, line 1, delete " or 2".

Claim 4, line 1, change "any preceding claim" to --Claim 1--.

Claim 5, line 1, change "any preceding claim" to --Claim 1--.

Claim 6, line 1, change "any preceding claim" to --Claim 1--.

Claim 7, line 1, change "any preceding claim" to --Claim 1--.

Claim 10, line 1, delete " or 9".

Claim 12, line 1, change "any of Claims 8 to 10" to --Claim 8--.

Claim 13, line 1, change "any of Claims 9 to 12" to --Claim 9--.

## **REMARKS**

This preliminary amendment is being filed to insert the amended sheets of claims as submitted in the international application from which this application is a national phase of. This preliminary amendment is also being filed to delete the multiple-dependency of claim 3, 4, 5, 6, 7, 10, 12, and 13. Entry of this preliminary amendment is respectfully requested.

Respectfully submitted,

MCDERMOTT, WILL & EMERY

Sene 3. Rubinson

Registration No. 33,351

600 13<sup>th</sup> Street, N.W. Washington, DC 20005-3096 (202) 756-8000 GZR:dtb

**Date: March 15, 2001** Facsimile: (202) 756-8087

#### **CLAIMS**

- A method of audio signal processing comprising providing an auxiliary data signal for communicating with a decoded audio signal, the auxiliary data signal comprising information for use in re-encoding the decoded audio signal, the method being characterised by providing signature information representative of the decoded audio signal for use in detecting a change in the decoded audio signal, wherein the signature information contains information enabling significant changes in the audio signal to be detected but minor changes which are unlikely to affect coding substantially to be tolerated while making use of information for use in re-encoding contained in the auxiliary data signal.
- 2. A method according to Claim 1, wherein the signature information is included in the auxiliary data signal.
- 3. A method according to Claim 1 or 2, wherein the signature information includes a checksum calculated from decoded audio samples.
- 4. A method according to any preceding claim, wherein the signature information enables a match, or a partial match, between the decoded audio signal and the signature information to be detected when the decoded audio signal has undergone a minor change which is unlikely to affect coding substantially.
- A method according to any preceding claim, wherein the signature information includes statistical information derived from the decoded audio signal.
- 6. A method according to any preceding claim, wherein the decoded audio signal has a mean signal level and the signature information includes a measure of said mean signal level.

and the Hartfell Market

- A method according to any preceding claim, wherein the signature information includes a measure of standard deviation of sample values from the mean.
- A method of re-encoding a decoded audio signal comprising receiving the 8. decoded audio signal, an auxiliary data signal containing information for use in re-encoding the decoded audio signal and re-encoding the decoded audio signal based on re-encoding information contained in the auxiliary data signal, characterised by providing a signature information signal containing signature information representative of the decoded audio signal for use in detecting a change in the decoded audio signal, wherein the signature information contains information enabling significant changes in the audio signal to be detected but minor changes which are unlikely to affect coding substantially to be tolerated while making use of information for use in reencoding contained in the auxiliary data signal; checking whether the received signature information matches the decoded audio signal; and wherein said re-encoding the decoded audio signal is based on re-encoding information contained in the auxiliary data signal if the signature information matches.
- 9. A method as claimed in Claim 8, wherein the signature information is combined with the auxiliary data signal.
- 10. A method according to Claim 8 or 9, wherein checking comprises deriving further signature information from the received audio signal and comparing the derived further signature information to the received signature information.
- 11. A method according to Claim 10, wherein comparing comprises comparing any difference between the derived and received signature information to at least one threshold.

15.

- ,12. A method according to any of Claims 8 to 10, wherein all of the auxiliary data signal is used for re-encoding if a perfect or near-perfect match is detected.
  - 13. A method according to any of Claims 9 to 12, wherein some of the auxiliary data signal is used for re-encoding if a partial match is detected.
  - 14. Apparatus for decoding a compression encoded audio signal comprising means for decoding the compression encoded audio signal to produce a decoded audio signal; and means for providing an auxiliary data signal containing information for use in re-encoding the decoded audio signal; characterised by means for providing signature information representative of the decoded audio signal for use in detecting a change in the decoded audio signal, wherein the signature information contains information enabling significant changes in the audio signal to be detected but minor changes which are unlikely to affect coding substantially to be tolerated while making use of

information for use in re-encoding contained in the auxiliary data signal.

Apparatus for re-encoding a decoded audio signal comprising: means for receiving said decoded audio signal together with auxiliary information for use in re-encoding the signal; and means for re-encoding the decoded audio signal based on the auxiliary information, characterised in that: the means for receiving is arranged to receive signature information wherein the signature information contains information enabling significant changes in the audio signal to be detected but minor changes which are unlikely to affect coding substantially to be tolerated while making use of information for use in re-encoding contained in the auxiliary data signal, the apparatus further comprising means for checking whether the decoded audio signal matches the signature information; and wherein said means for re-encoding is arranged to re-encode the decoded audio signal based on the auxiliary information if the decoded audio signal matches the signature information.

16. In combination, a decoded, previously compression encoded, audio signal, an auxiliary data signal comprising information for use in re-encoding the decoded audio signal, and a signature information signal containing signature information representative of the decoded audio signal for use in detecting changes in the decoded audio signal, wherein the signature information contains information enabling significant changes in the audio signal to be detected but minor changes which are unlikely to affect coding substantially to be tolerated while making use of information for use in re-encoding contained in the auxiliary data signal.

PCT/GB99/03153

JC02 Rec'd PCT/PTO 1 5 MAR 2001

WO 00/18046

TANDEM AUDIO COMPRESSION

The present invention relates to audio compression, and particularly to decoding and recoding of compressed audio signals.

5

Earlier British Broadcasting Corporation International Application WO-A-98/33284, the entire disclosure of which is incorporated herein by reference, discloses a method of decoding and recoding digital audio which results in reduced impairment in quality, by communicating an auxiliary signal containing information concerning coding decisions.

10

A problem can arise, however, that the decoded audio is processed so that the additional information no longer becomes helpful in the recoding process. Our earlier application suggests either disabling the auxiliary data signal in the event of such processing or adding a tell-tale signal to the decoded audio to indicate that such processing has occurred.

15

Whilst the above system works well, it has been found that an alternative arrangement may offer improved results in certain circumstances.

20

25

According to a first aspect, the invention provides a method of audio signal processing comprising providing an auxiliary data signal for communicating with a decoded audio signal, the auxiliary data signal comprising information for use in reencoding the decoded audio signal, the method further comprising providing signature information representative of the decoded audio signal for use in detecting a change in the decoded audio signal.

30

In this way, rather than having to identify a tell-tale in the decoded audio, a change in the decoded audio can be automatically detected at the point of recoding by comparing the signature information to the decoded audio. Preferably, the signature information is communicated with the auxiliary data stream. Since the auxiliary

10

15

20

25

30

WO 00/18046 PCT/GB99/03153

data stream must, in any event, be read in order to effect re-encoding based on the auxiliary data stream, this may simplify processing.

The signature information may include a checksum derived from the values of the decoded audio samples. This may enable identification of even very minor changes, and allow maintenance of absolute purity of the audio signal.

Alternatively, the signature information may include statistical information derived from the decoded audio signal, for example mean signal level and, optionally, standard deviation of sample values from the mean. This may enable significant changes in the audio signal to be detected, whilst rendering the system insensitive to minor modifications. Thus, the signature information may contain information enabling significant changes in the audio signal to be detected but minor changes to be ignored. Similarly, the signature information may enable a match, or a partial match, to be detected when the decoded audio signal has undergone a minor change.

The method may further comprise detecting whether the signature information matches the decoded audio, for example by comparing a signature derived from the decoded audio signals to the communicated signature information and detecting whether the difference between the derived and communicated signature exceeds a predetermined threshold. If the signature matches, then the decoded signals can be re-encoded using the auxiliary signal, for example in the manner described in our earlier application WO-A-98/33284. If the signature does not match, the decoded signal can be re-encoded without using the auxiliary data signal, or using only a part of the auxiliary data signal.

The auxiliary signal may be derived together with the signature information from a received compression-encoded audio signal as part of compression decoding of the compression encoded audio signal.

The auxiliary data signal may be selected from the signals described in our earlier

application WO-A-98/33284.

Further aspects and preferred features are set out in the claims, to which reference should be made.

5

An embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings in which Fig. 1 is a schematic diagram of cascaded decoding and re-encoding processes according to a preferred embodiment.

10

Referring to Fig. 1, a compressed audio signal is passed to a decoder 10 which extracts auxiliary information for use in re-coding the signal and decompresses the signal to produce a decoded audio signal and an auxiliary signal. In the embodiment shown, the decoded audio signal and auxiliary signal are output separately. The decoded audio signal passes through studio equipment which may process the signal and is re-encoded in an encoder 20. The auxiliary signal extracted is passed to the encoder 20 for use in re-encoding.

15

Thus far, the apparatus may be as described in our earlier WO-A-98/33284, the entire disclosure of which is incorporated herein by reference, with particular reference to Fig. 2 and the related description.

20

In the embodiment shown, the auxiliary signal is communicated separately from the decoded audio signal. As an alternative, for example as described in WO-A-98/33284, the auxiliary signal may be communicated with the decoded audio signal; one arrangement suitable for achieving this is described with reference to Fig. 3 of WO-A-98/33284.

25

30

In accordance with the present embodiment, in addition to auxiliary information for use in re-encoding, signature information representative of the decoded audio signal is calculated by the decoder 10 and communicated as part of the auxiliary data signal.

10

15

20

25

30

The signature information may comprise, for example, a checksum calculated for individual audio samples or for a predetermined number of audio samples. The provision of a checksum enables accurate verification of faithful reproduction of the audio signal. Alternatively, the signature information may comprise a measure derived from the decoded audio signal, for example a statistical measure such as the mean signal level, and optionally the standard deviation (or other measure, such as variance or the like) of samples from the mean. Provision of statistical or other information may enable minor changes (by which is meant changes which are unlikely to affect coding substantially) to be tolerated while making use of previous coding information. Provision may be made for identifying a partial match based on closeness of match so that some or all information may be used.

The auxiliary signal and the signature signal are preferably conveyed together as a single digital data signal. They can advantageously be conveyed in the user bits of an AES-3 bitstream.

In the encoder 20, the signature information received is compared to a further signature calculated from the decoded audio signal which has been processed by the studio equipment. If the signatures match within a predetermined threshold, reencoding is performed using the auxiliary information, for example in the manner described in WO-A-98/33284.

If the signatures do not match, re-encoding is performed without reference to the auxiliary signal.

The setting of the threshold within which a match is detected will depend on the nature of the auxiliary signal and also the nature of the signature information. The threshold should be set so that the auxiliary information is used whenever it might assist the re-coding process but discarded when it will not improve the fidelity of the overall cascaded decoding and re-encoding processes.

10

15

20

25

30

In certain cases, rather than a "yes/no" comparison, the re-encoding process may be arranged to take some, but not all, of the auxiliary information into account or to modify a "blind" re-encoding process based on the auxiliary information when an imperfect signature match is detected, but not to discard the auxiliary information entirely.

By way of background, we will summarise certain examples of auxiliary information and ways in which it may be carried (as described in WO-A-98/33284).

Examples of signals that could comprise the auxiliary data are:

- 1. The coded audio signal at the input to the decoder (D1, D2, etc.). This contains not only audio-related data and the PTS but also certain auxiliary information such as programme-associated data (PAD), which may need to be copied into the coded signal at the output from the studio area, and error protection. Depending upon the circumstances, such a signal would enable the coder (C) to substitute the original coded signal for the recoded PCM signal, or to re-code the PCM signal with blocks of audio data resembling closely the blocks within the original coded signal, as described above. Conveying the coded audio signal to the coder provides the widest range of options for re-coding with minimal additional impairment of the audio.
- 2. The coded audio samples at the input to the decoder minus the quantised audio samples (which can be re-created identically from the PCM audio signal). This is a signal in which the positions of the frame boundaries of the original coded signal are indicated relative to the linear audio samples in the PCM signal, and from which the positions of the blocks of data within the frames may be deduced, together with information on the allocation of bits to the various components of the coded signal (sometimes known as "bit-allocation data"), scale factors, block lengths (in coding schemes where, this

10

15

20

25

is relevant), the PTS, and any other data relevant to the coding system in use.

3. A signal similar to that described in "2" above, but containing a subset of the information described (e.g. just the positions of the frame boundaries).

As mentioned above, the signature information is preferably carried with the auxiliary data. It may however be carried independently, for example along a dedicated channel.

The following are ways in which the auxiliary data signal might be transported with the PCM audio. The signature information, if not combined with the auxiliary data signal, may be transported along another of these (or other) possible routes. The routes are:-

- 1. In the auxiliary sample bits of the ITU-R Rec. 647 bitstream. At the studio standard sampling frequency of 48 kHz, a total bit rate of 384 kbit/s is available in the auxiliary sample bits of both "X" and "Y" subframes. This method is ideal for conveying the auxiliary data between different items of equipment but there is some uncertainty concerning the way in which studio equipment might treat these auxiliary sample bits. For example, the studio equipment may not route these bits through to the output with the PCM audio, or it may not delay these bits by the same amount as the PCM audio. In either case, some modification of the studio equipment, or of the environment around it, may be necessary.
- 2. In the least significant bits (l.s.b.) of the PCM audio sample words of the ITU-R Rec. 647 bitstream. The bits can be inserted into active audio or may be additional bits. Depending upon the resolution of the studio equipment these may the same as the auxiliary sample bits (these are the

1.s.b if the Rec. 647 signal is configured to carry 24-bit audio sample words) or the least significant bits within the part of the subframe reserved for 20-bit audio sample words (these are the same bits that carry the 20 most significant bits of 24-bit sample words). The data can be carried as the least significant bit of 16 bit audio. Carrying the auxiliary data in the l.s.b. of the audio sample words overcomes the problems of routing within the studio equipment and care will be taken to ensure that the auxiliary data signal is inaudible. The studio equipment needs to be transparent to audio sample words of at least 20 bits. If necessary, the audibility of the auxiliary data signal could be reduced by scrambling (e.g. by the modulo-2 addition of a pseudorandom binary sequence, or the use of a self-synchronising scrambler). Alternatively, it could be removed altogether by truncating the audio sample words to the appropriate length (i.e. to exclude the auxiliary data).

15

10

5

3. In the user data bits of the ITU-R Rec. 647 bitstream. Taking the user data bits from both "X" and "Y" subframes provides a channel with a bit rate of only 96 kbit/s. In many applications this is unlikely to be sufficient to carry the complete coded audio signal. It would be sufficient to signal the positions of frame boundaries, and to carry some other information extracted from the coded audio. With this method there is uncertainty concerning the way in which studio equipment might treat the user data.

25

20

4. In the upper part of the audio spectrum, at frequencies higher than those of the audible components of the signal. For this purpose, the PCM audio signal would be low-pass filtered, and the coded auxiliary data signal added above the passband occupied by the audible signal. A particularly ingenious way of doing this, when the studio area is receiving MPEG audio coded signals, would be to use an MPEG analysis subband filterbank with the reciprocal synthesis filterbank at the insertion units. At 48 kHz sampling

30

frequency, the audio passband extends almost up to 24 kHz. In MPEG audio coding this passband is divided into 32 equally-spaced subbands, each with a bandwidth of 750 Hz. The upper five subbands are not used, and the audio is thus effectively low-pass filtered to 20.25 Khz. The auxiliary data could be inserted into the upper subbands, and would be carried in the upper part of the spectrum of the PCM audio signal, to be extracted by another MPEG analysis filterbank at the splitter. The PCM signal applied to the coder would not need further filtering to remove the auxiliary data, as this would happen in the analysis filterbank in the coder itself.

10

5

5. The auxiliary signal might be a low-level known pseudo random binary sequence (prbs) added to the audio. The prbs would be synchronised in some way with the audio frame boundaries and may be modulated with additional data where possible. It is also possible to subtract the prbs from the data prior to final transmission or monitoring.

15

It has been explained that under certain circumstances it is appropriate to perform partial decoding and re-encoding. In the appended claims the terms decoding and re-encoding should be taken as including partial decoding and re-encoding, respectively.

20

It will be appreciated that there are numerous ways in which the invention can be applied to assist in re-encoding of a previously decoded signal. In particular, it is to be noted that the present invention is not specifically limited to a basic decoding and recoding process as described in WO-A-98/33284, the disclosure of which is provided purely by way of an exemplary system in which the invention may be employed.

30

25

Each feature disclosed herein may be provided independently, unless otherwise stated.

30

5

#### **CLAIMS**

- 1. A method of audio signal processing comprising providing an auxiliary data signal for communicating with a decoded audio signal, the auxiliary data signal comprising information for use in re-encoding the decoded audio signal, the method further comprising providing signature information representative of the decoded audio signal for detecting a change in the decoded audio signal.
- 10 2. A method according to Claim 1, wherein the signature information is included in the auxiliary data signal.
  - 3. A method according to Claim 1 or 2, wherein the signature information includes a checksum calculated from decoded audio samples.
  - 4. A method according to any preceding claim, wherein the signature information contains information enabling significant changes in the audio signal to be detected but minor changes to be ignored.
- 20 5. A method according to any preceding claim, wherein the signature information enables a match, or a partial match, to be detected when the decoded audio signal has undergone a minor change.
- 6. A method according to any preceding claim, wherein the signature information includes statistical information derived from the decoded audio signal.
  - 7. A method according to any preceding claim, wherein the signature information includes a measure of the mean decoded audio signal level.
  - 8. A method according to any preceding claim, wherein the signature

5

10

information includes a measure of standard deviation of sample values from the mean.

- 9. A method of re-encoding a decoded audio signal comprising receiving the decoded audio signal, an auxiliary signal containing information for use in re-encoding the decoded audio signal and a signature information signal; checking whether the received signature information matches the decoded audio signal; and re-encoding the decoded audio signal based on re-encoding information
  - 10. A method as claimed in Claim 9, wherein the signature information is combined with the auxiliary data signal.

contained in the auxiliary data signal if the signature information matches.

- 11. A method according to Claim 9 or 10, wherein checking comprises deriving further signature information from the received audio signal and comparing the derived further signature information to the received signature information.
- 20 12. A method according to Claim 11, wherein comparing comprises comparing any difference between the derived and received signature information to at least one threshold.
- 13. A method according to any of Claims 9 to 11, wherein all of the auxiliary data signal is used for re-encoding if a perfect or near-perfect match is detected.
  - 14. A method according to any of Claims 9 to 13, wherein some of the auxiliary data signal is used for re-encoding if a partial match is detected.
  - 15. Apparatus for decoding a compression encoded audio signal comprising

means for decoding the signal; means for extracting an auxiliary data signal containing information for use in re-encoding the signal; and means for deriving signature information representative of the decoded signal for use in detecting a change in the decoded signal.

5


16. Apparatus for re-encoding a decoded audio signal comprising:

means for receiving said decoded audio signal together with auxiliary information for use in re-encoding the signal and signature information; means for checking whether the decoded audio information matches the signature information; and means for re-encoding the decoded signal based on the auxiliary information if the signature matches.

10

15

17. In combination, a decoded previously compression encoded audio signal, an auxiliary data signal comprising information for use in re-encoding the decoded audio signal, and a signature information signal representative of the decoded audio signal for use in detecting changes in the decoded audio signal.



			J. 800 y.				
COMBINE	D DECLARATION FO	OR PATENT APPLICATION AN	D POWER OF ATTORNEY	Attorney's Docket Number			
(Includes Re	ference to PCT International	Application(s)		50060-044			
As below nar	med inventor, I hereby decla	re that:					
My residence, post office address and citizenship are as stated below next to my name,							
		nventor (if only one name is listed below) thich a patent is sought on the invention e	or an original, first and joint inventor (if pluentitled:	ural names are listed below) of the			
TANDEM AU	IDIO COMPRESSION	»-					
the specificat	ion of which:						
	is attached hereto.						
⊠	Was filed as United States application Serial No.						
	onMarch 15, 2001						
	and was amended on	March 15, 2001		(if applicable).			
	was filed as PCT international application Number PCT/GB99/03153						
The state of the s	on September 23, 1999						
	and was amended under F		(if applicable).				
I hereby state referred to ab		nderstand the contents of the above-iden	tified specification, including the claims, a	s amended by any amendment			
l acknowledg §1.56.	e the duty to disclose inform	ation which is known to me to be materia	al to patentability in accordance with Title	37, Code of Federal Regulations,			
I haraby clain	n foreign priority benefits un	der Title 35 United States Code 8110(a)	-(d) or Section 365(b) of any foreign and/	or international application(s) for			
patent or inve America listed designating a	entor's certificate or Section d below and have also ident at least one country other tha	365(a) of any PCT international application fied below any foreign application(s) for p in the United States of America filed by m	on(s) designating at least one country other patent or inventor's certificate or any PCT ne on the same subject matter having a fil	er than the United States of international application(s)			
application(s)	of which priority is claimed:						
PRIOR FOR	EIGN/PCT APPLICATION(S	S) AND ANY PRIORITY CLAIMS UNDER	R 35 U.S.C. 119:				
	COLINTRY	ADDI ICATION NI MADED	DATE OF FILING	DDIODITY OF AIMED			
COUNTRY  (If PCT_indicate "PCT")		APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119			
(If PCT, indicate "PCT")  Great Britain		9820757.4	September 23, 1998	Yes □ No			
Great Diltain		0020707.7	- COPICITIDO 20, 1000	KN100 PM100			
I hereby clain	n the benefit under 35 USC	§119(e) of any United States provisional	application(s) listed below.	L			
	VISIONAL APPLICATION(S						
,		on Number	Filing I	Date			

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s), or §365(c) of any PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application.

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:									
U.S. APPLICATIONS					STATUS (Check One)				
	U.S. Application Numl	ber	U.S. Filing Date -		\ \frac{7}{3}	Patented	Pending	Abandoned	
				<b>&amp;</b> ~~	0,4				
					,``				
					,	**			
	PCT APP		DESIGNATING	T					
PC.	T Application No.	PCT F	Filing Date U.S. Serial Numbers Assigned (if any)						
							1		
DOIN'E	DOE ATTORNEY A			ppoint the following attorney(	<u> </u>				
Lawren 46,072 Willem Joseph Lupa, N No. 27 Wester Robert Send (	McDERMOTT, WILL & EMERY  (name and telephone number)								
201	Washington, D.C. Full Name of Inventor	-	Family Name		First Given Name		Second Giver	n Name	
上型			MASON		Andrew		James		
201	Residence and Citizenship		City		State or Foreign Country,		Country of C	itizenship	
lai lai			Surrey		Great Britain		Great Britain	Great Britain	
£	Post Office Address		Post Office Address		City		State & Zip C	Code/Country	
		1 Meadow Way		Reigate, Surrey RH2 8DP		Great Britain			
I hereby declare that all statement made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.  Signature of inventor 201:									
Date	M lus	sin							
Dale	5 June	200	)						